

Rack Safety Net Instructions

Each net ships with all hardware needed to install.



SECTION 1: Kit Contents



Eye bolts




Washers



Nylock Nuts



Drill Bits
2 sizes



Cable




Turnbuckle



Snap Hooks



Wire Rope Clips




Netting


NOTE: Each system ships with the correct amount of hardware for the size ordered. Each eye bolt should have 1 washer and 1 nylock nut.

SECTION 2: The Instructions

1. Examine upright openings.



Teardrop





Slot



Circle

2. Depending on the size and shape, drilling may be required. Choose the drill bit appropriate for your upright and make a hole for the eye bolt.



3. Insert eye bolt into the attachment point (tear, slot, circle, or drilled hole).
4. Place washer and nylock nut on the back of the eye bolt.
5. Use socket to tighten nylock nut onto the eye bolt.

6. Repeat with each eye bolt starting at 4 corners and center remaining eye bolts evenly as needed.

7. Create end loop with cable and wire rope clips through bottom corner eye bolt to create an anchor point.

8. Feed cable through the eye bolts around the perimeter of the area to be protected.

9. Create a loop on the open end of the cable around one end of the turnbuckle. Hook the turnbuckle to the eye bolt and tighten.

10. Use your snap hooks to attach the net to the wire rope border fastening each corner to an eye bolt. Fastening the corners to the eye bolts provide stability while allowing the net to act in a curtain like manner to slide open for access.

